

C

Reg. No. :

--	--	--	--	--	--	--	--	--	--

Question Paper Code: 57101

B.E./B.Tech. DEGREE EXAMINATION, NOV 2019

Seventh Semester

Civil Engineering

15UCE701 -DESIGN OF REINFORCED CONCRETE AND BRICK

MASONRY STRUCTURES

(Regulation 2015)

(IS 456:2000, IS 1905 - 1987, IS 3370 : Part-II and Part-IV are permitted)

Duration: Three hours

Maximum: 100 Marks

Answer ALL Questions

PART A - (5 x 1 = 5 Marks)

- Rankine's theory of lateral pressure was extended to other soil by _ CO1- R
(a) Resal and Bell (b) Mohr (c) Terzaghi (d) All the above
- Dome in water tank is provided to achieve CO2- R
(a) Maximum strength (b) Maximum storage
(c) Minimum storage (d) Minimum hoop stress
- The decorative cap to the top of a newel post is called: CO3- R
(a) Finials (b) Fillet (c) Easing (d) Apron
- In a simply supported slab, alternate bars are curtailed at CO4- R
(a) $1/4^{\text{th}}$ of the span (b) $1/5^{\text{th}}$ of the span (c) $1/6^{\text{th}}$ of the span (d) $1/7^{\text{th}}$ of the span
- The minimum thickness of the flat slab is taken as CO5- R
(a) $L/32$ for end panels without drops (b) $L/36$ for end panels without drops
(c) $L/36$ for interior panels without drops (d) All the above

PART – B (5 x 3 = 15 Marks)

6. Name the different types of retaining walls. CO1- R
7. List the factors for designing a water tank. CO2-U
8. What are the components of flat slab? CO3- R
9. State the principle of virtual work. CO4- R
10. What is meant by lateral support? CO5- R

PART – C (5 x 16= 80 Marks)

11. (a) Design a reinforced concrete cantilever type retaining wall , CO1- App (16)
having a 5m full stem. The wall retains the soil with its top. The soil weighs 18000N/m^3 , and has an angle of repose 30° . The SBC of soil is 200KN/m^2 . Use M20 grade concrete and Fe 415 Steel.

Or

- (b) Design a counter fort retaining wall for the following data. CO1- App (16)
Height of the wall above the ground level = 6m
SBC of the soil = 160KN/m^2 .
Angle of friction = 33° .
Density of the soil = 16KN/m^3 .
Spacing of the counter fort = 3m c/c
Use M20 grade concrete and Fe 415 Steel.

12. (a) Design a underground water tank of internal dimension CO2- E (16)
 $6\text{m} \times 3\text{m} \times 3\text{m}$. The soil surrounding the tank always remains dry. The tank shall be provided with a roof slab. The soil weighs 16000 N/m^2 , having an angle of repose 30° . Use M20 grade concrete and Fe 415 Steel.

Or

- (b) A reinforced concrete dome of 6m base diameter with a rise of CO2- E (16)
1.25m is to be designed for a water tank . The uniformly distributed live load including finishes on dome may be taken as 2KN/m^2 . Adopt M20 concrete and grade one steel . Design the dome and the ring beam , permissible tensile stress in steel is 100N/mm^2 .

13. (a) Design a interior panel of flat slab with drops for an office floor CO3- U (16)
to suit the following data.
Size of floor = 20m X 20m
Size of panel = 5m X 5m
Loading class = 4 KN/m²
Grade of concrete = M 20
Grade of steel = Fe 415

Or

- (b) Explain the step by step procedure for reinforced concrete walls. CO3- U (16)
14. (a) Design a rectangular slab 5mx4m in size and simply supported at CO4- Ana (16)
the edges to support a service live load of 4KN/m². Assume
coefficient of orthotropy as 0.7 Use M20 grade concrete and Fe
415 Steel.

Or

- (b) Design a reinforced circular slab for the following data . CO4- Ana (16)
Diameter of the slab = 5.5m
Service load = 4KN/m².
Floor finish load = 1KN/m².
The slab is simply supported along the edge. Use M20 grade
concrete and Fe 415 Steel.
15. (a) Design a interior cross wall with axially loaded and on stiffened CO5- E (16)
solid wall constructed in a two storied building to carry 100mm
thick RCC slabs with 3m ceiling height. It support a 2.65 m wide
slab with live load on roof = 1.5KN/m². Live load on floor =
2KN/m², weight of 80mm thick terrace = 1.96KN/m², weight of
floor finish = 0.8KN/m².

Or

- (b) Design an interior wall of two storied building load due to CO5- E (16)
unequal short spans of roof / floor of 4m and 3m , on either side
of the wall. The height of each storey is 3m , assume the intensity
of loading as i) from roof = 6KN/m² and ii) from floor =
4KN/m².

