A		Reg. No. :						
		Question Pape	r Code: 53302					
B.E./B.Tech. DEGREE EXAMINATION, NOV 2019								
Third Semester								
Electrical and Electronics Engineering								
15UEE302 - DC MACHINES AND TRANSFORMERS								
(Regulation 2015)								
Dur	ation: Three hours		Ma	aximum: 100 Marks				
Answer ALL Questions								
	PART A - $(10 \text{ x } 1 = 10 \text{ Marks})$							
1.	Permanent magnets a	are normally made of		CO1- R				
	(a) Alnico alloys	(b) Aluminum	(c) Cast Iron	(d) Wrought Iron				
2.	Energy stored by a coil is doubled when its current is increased by present. CO1- R							
	(a) 25	(b) 50	(c) 41.4	(d) 100				
3.	A transformer core is	s laminated to reduce		CO2- R				
	(a) Hysteresis loss		(b) Eddy current loss					
	(c) Copper loss		(d) All the above losses					
4.	A transformer cannot raise or lower the voltage of DC supply because CO2- R							
	(a) More losses in Do	С	(b) No windage losses					
	(c) Rate of change of	flux is zero	(d) Static device					
5.	An electro-mechanic	al energy conversion	device is one which converts	CO3- R				
	(a) Electrical energy to mechanical energy only							
	(b) Mechanical energy to electrical energy only							
	(c) All of the mention	ned						
	(d) None of the ment	ioned						

6.	What is the coupling field used between the electrical and mechanical systems in an energy conversion devices?							
	(a) Magnetic field	(b) Electric field						
	(c) Magnetic field or Electric field	(d) None of the mentioned						
7.	Which of the following law can be used to determine the direction of rotation of							
	DC Generator?							
	(a) Lenz law	(b) Faradays law						
	(c) Flemings left hand rule	(d) Flemings right hand rule	e					
8.	In a DC generator, the current to the external circuit is given through							
	(a) Commutator (b) Armature winding	(c) Solid connection	(d) Field winding					
9.	A DC series motor is that which		CO5- R					
	(a) has its fields winding consisting of thick wire and less turns							
	(b) has poor torque							
	(c) can be started easily without load							
	(d) almost constant speed							
10.	When the motor runs on no load, then		CO5- R					
	(a) Back emf is almost equal to applied voltage							
	(b) Back emf will be less than applied voltage	ge						
	(c) Back emf will be greater than applied voltage							
	(d) None of these							
$PART - B (5 \times 2 = 10 \text{ Marks})$								
11.	List out the properties of magnetic materials		CO1- R					
12.	Justify why transformer is rated in KVA		CO2- U					
13.	Differentiate single excited and multi excited system.							
14.	Recall the basic principle of a DC generator.							
15.	Provide the Importance of Laminated core?		CO5- R					

PART – C (5 x 16= 80Marks)

16.	(a)	(i) Derive the relation between mutual inductance and self inductances of two Magnetically coupled coils.	CO1- U	(8)
		(ii) Explain AC operation of magnetic circuits. Or	CO1- U	(8)
	(b)	Draw and Explain the typical magnetic circuit with air gap and derive the expression for air gap flux.	CO1- U	(16)
17.	(a)	Elaborate in detail about the sumpner's test conducted in transformers.	CO2- U	(16)
		Or		
	(b)	A 40 KVA transformer has iron loss of 450W and full load copper loss of 850W. If the power factor of the load is 0.8	CO2- U	(16)
		lagging, Calculate		
		(i) full load efficiency		
		(ii) the load at which maximum efficiency occurs and		
		(iii) the maximum efficiency		
18.	(a)	A steel ring has a mean diameter of 20cm, a cross section of	CO3- U	(16)
		25cm^2 and a radial air – gap of 0.8mm cut across it. When excited		
		by a current of 1A through a coil of 1000 turns wound o the ring		
		core, it produces an air-gap flux of 1mWb. Neglecting leakage		
		and fringing. Calculate		
		(i) Relative permeability of steel		
		(ii) Total reluctance of the magnetic circuit		
		Or		
	(b)		CO2 II	(16)
	(b)	Derive the equation for force developed in a singly excited magnetic field system.	003-0	(16)

19. (a) Sketch the construction of DC Generator and explain about CO4-U (16) various parts associated with it.

Or

- (b) Plot and explain various characteristics of DC generator. CO4- U (16)
- 20. (a) Narrate with the construction styles of DC motor types and CO5-U (16) explain in detail.

Or

(b) (i) A 220V series motor runs at 1500rpm when taking a line CO5-U (8) current of 20A. The resistance of armature and field windings are 0.4 Ω and 0.6 Ω respectively. If the current taken remains constant calculate the resistance necessary to reduce the speed to 500rpm.

(ii) What is the necessity of starters? Explain the functions of 3- CO5-U (8) point starters in detail.