

Reg. No. :

--	--	--	--	--	--	--	--	--	--

Question Paper Code: 49702

B.E. / B.Tech. DEGREE EXAMINATION, DEC 2020

Elective

Mechanical Engineering

14UME902 - GAS DYNAMICS AND JET PROPULSION

(Regulation 2014)

Duration: 1.15 hrs

Maximum: 30 Marks

PART A - (6 x 1 = 6 Marks)

(Answer any six of the following questions)

- In _____ regions, fluid velocity is equal to the sound velocity.
 - Incompressible flow
 - Subsonic flow
 - Sonic flow
 - Hypersonic flow
- Subsonic Converging passage of nozzle may be acted as
 - Subsonic diffuser
 - Sonic throat
 - Supersonic diffuser
 - Hypersonic diffuser
- For an isothermal flow in long constant area duct, _____ remains constant.
 - Static temperature
 - Viscosity
 - Friction factor
 - All the above
- The value of mach number of air at the maximum point of Rayleigh flow is
 - 0.5
 - 0.25
 - 0.75
 - 1
- The stagnation pressure across normal shock may
 - increase
 - decrease
 - remains constant
 - increase or decrease
- Shock can be develop in a _____ flow.
 - supersonic
 - subsonic
 - sonic
 - none of these

7. Propulsive efficiency is defined as the ratio of
- (a) Thrust power and fuel energy (b) Engine output and propulsive power
- (c) Propulsive power and fuel input (d) Thrust power and propulsive power
8. In jet engines, for the efficient production of large power, fuel is burnt in an atmosphere of
- (a) Vacuum (b) Atmospheric air
- (c) Compressed air (d) Oxygen alone
9. The thrust per unit weight flow rate of the propellant for a rocket engine is known as its
- (a) Specific impulse (b) Specific propellant consumption
- (c) Weight flow co-efficient (d) Thrust co-efficient
10. Theoretically the maximum achievable speed by a body in space is equal to
- (a) 1,97,600 km/s (b) 2,97,600 km/s
- (c) 330 m/s (d) 330 km/s

PART – B (3 x 8= 24 Marks)

(Answer any three of the following questions)

11. The pressure, temperature and Mach number at the entry of a flow passage are 2.45 bar, 26.5°C and 1.4 respectively. If the exit Mach number is 2.5 determine for adiabatic flow of perfect gas ($\gamma=1.3$, $R=0.469$ kJ/kg K). (8)
- (i) stagnation temperature
- (ii) maximum velocity
- (iii) mass flow rate
- (v) Area of cross-section at exit Or
12. A circular duct passes 8.25 kg/s of air at an exit Mach number of 0.5. The entry pressure and temperature are 345 kPa and 38⁰C respectively and the co-efficient of friction is 0.005. If the Mach number at entry is 0.15, determine: (i) The diameter of the duct (ii) Length of the duct (iii) Pressure and temperature at exit, and (iv) Stagnation pressure loss. (8)

13. An Aircraft flies at a Mach number of 1.1 at an altitude of 15,000 meters. The compression in its engine is partially achieved by a normal shock wave standing at the entry of the diffuser. Determine the following for downstream of the shock: (i) Mach number (ii) Temperature of the air (iii) Pressure of the air (iv) Stagnation pressure loss across the shock. (8)
14. Illustrate the working of ramjet engine and depict the various thermodynamic processes occurring in it on $h-s$ diagram. Write down its main advantages and disadvantages. (8)
15. A rocket nozzle has a throat area of 18cm^2 and combustor pressure of 25bar. If the specific impulse is 127.42sec and the rate of flow of propellant is 44.145N/s, determine the thrust coefficient, propellant weight flow coefficient, specific propellant consumption and characteristic velocity. (8)