

Reg. No. :

--	--	--	--	--	--	--	--	--	--

**Question Paper Code: 33073**

B.E. / B.Tech. DEGREE EXAMINATION, NOV 2017

Third Semester

Mechanical Engineering

01UME303 - ENGINEERING THERMODYNAMICS

(Use of steam tables, charts may be permitted)

(Regulation 2013)

Duration: Three hours

Maximum: 100 Marks

Answer ALL Questions

PART A - (10 x 2 = 20 Marks)

1. What is PMM1?
2. What is heat?
3. What do you mean by "Clausius Inequality"?
4. State the Clausius statement of the second law of thermodynamics.
5. What is triple point?
6. What is degree of superheat?
7. State Gibbs function.
8. Write Clausius Clapeyron equation.
9. State Dalton's law of partial pressure.
10. Define relative humidity.

PART - B (5 x 16 = 80 Marks)

11. (a) Air flows steadily at the rate of  $0.4 \text{ kg/s}$  through an air compressor, entering at  $6 \text{ m/s}$  with a pressure of  $1 \text{ bar}$  and a specific volume of  $0.85 \text{ m}^3/\text{kg}$  and leaving at  $4.5 \text{ m/s}$  with a pressure of  $6.9 \text{ bar}$  and a specific volume of  $0.16 \text{ m}^3/\text{kg}$ . The internal energy of air leaving is  $88 \text{ kJ/kg}$  greater than that of the air entering. Cooling water in a jacket surrounding the cylinder absorbs heat from the air at the rate of  $59 \text{ W}$ . Calculate the power required to drive the compressor and the inlet and outlet cross sectional areas. (16)

Or

- (b) Derive the general energy equation for a steady flow system and apply the equation to a nozzle and derive an equation for velocity at exit. (16)

12. (a) Show that the maximum work obtainable from two finite bodies at temperatures

$$T_1 \text{ and } T_2 \text{ is } C_p (\sqrt{T_1} - \sqrt{T_2})^2. \quad (16)$$

Or

- (b) A reversible engine operates between a source at  $972^\circ\text{C}$  and two sinks, one at  $127^\circ\text{C}$  and another at  $27^\circ\text{C}$ . The energy rejected is same at both the sinks. What is the ratio of heat supplied to the heat rejected? Also calculate the efficiency. (16)

13. (a) A vessel of volume  $0.04 \text{ m}^3$  contains a mixture of saturated water and saturated steam at a temperature of  $250^\circ\text{C}$ . The mass of the liquid present is  $9 \text{ kg}$ . Find the pressure, the mass, the specific volume, the enthalpy, the entropy and the internal energy of the mixture. (16)

Or

- (b) A steam turbine with an internal efficiency of  $90\%$  receives steam at  $7 \text{ MPa}$  and  $550^\circ\text{C}$  and exhausts at  $20 \text{ kPa}$ . Determine the turbine work, exhaust enthalpy and exit quality of the steam. (16)

14. (a) Explain the flow process of a real gas through a throttle valve. Derive the expression for Joule Thomson coefficient and get its value for an ideal gas. (16)

Or

(b) Prove that  $C_p - C_v = -T \left( \frac{\partial V}{\partial T} \right)_P^2 \left( \frac{\partial P}{\partial V} \right)_T$  from Tds equations. (16)

15. (a) Saturated air at  $20^\circ\text{C}$  at a rate of  $1.167 \text{ m}^3/\text{s}$  is mixed adiabatically with the outside air at  $35^\circ\text{C}$  and 50% relative humidity at a rate of  $0.5 \text{ m}^3/\text{s}$ . Assuming adiabatic mixing condition at 1 atm, determine specific humidity, relative humidity, dry bulb temperature and volume flow rate of the mixture. (16)

Or

- (b) In an adiabatic mixing of two streams, derive the relationship among the ratio of mass of streams, ratio of enthalpy change and ratio of specific humidity change. (16)
-

