

Reg. No. :

--	--	--	--	--	--	--	--	--	--

Question Paper Code: 34705

B.E. / B.Tech. DEGREE EXAMINATION, MAY 2018

Fourth Semester

Mechanical Engineering

01UME405 – STRENGTH OF MATERIALS

(Regulation 2013)

Duration: Three hours

Maximum: 100 Marks

Answer ALL Questions.

PART A - (10 x 2 = 20 Marks)

1. Define proof resilience and modulus of resilience.
2. Define: Resilience.
3. What do you mean by the point of contraflexure?
4. Write the equation for the simple bending theory.
5. Distinguish between closed coil helical spring and open coil helical spring.
6. What kind of stress introduced when an axial load acts on a closed and open coiled spring?
7. State the limitations of Euler's formula.
8. State the condition for the use of Macaulay's method.
9. Define principal planes and principal stresses.
10. What are types of stress in a thin cylindrical vessel subjected to internal pressure?

PART - B (5 x 16 = 80 Marks)

11. (a) An aluminium cylinder of diameter 60 mm located inside a steel cylinder of internal diameter 60 mm and wall thickness 15 mm. The assembly is subjected to a compressive force of 200 kN. What are the forces carried and stresses developed in steel and aluminium? Take Modulus of elasticity for steel as 200 GPa and aluminium as 70 GPa. (16)

Or

- (b) A bar of 30mm dia is subjected to a pull of 60kN. The measured extension on a gauge length of 200mm is 0.09mm and the change in dia 0.0039 mm. calculate the poisson, s ratio and the value of elastic constants. (16)
12. (a) A Simply supported beam 6 m span carries an UDL of 20 kN/m for left half of span and two point loads of 25 kN and 35 kN at 4 m and 5 m from left support. Find maximum shear force (SF) and bending moment (BM) and their location drawing SF and BM diagrams. (16)

Or

- (b) Derive the shear stress equation for a rectangular cross section. (16)
13. (a) It is required to design a closed coiled helical spring which shall deflect 1mm under an axial load of 100 N at a shear stress of 90 MPa. The spring is to be made of round wire having shear modulus of 0.8×10^5 MPa. The mean diameter of the coil is 10 times that of the coil wire. Find the diameter and length of the wire. (16)

Or

- (b) A helical spring of circular cross-section wire 18 mm in diameter is loaded by a force of 500N. Determine the maximum shear stress in the material of the spring. What number of coils must mean coil diameter of the spring is 125mm. The modulus of rigidity is 80 kN/mm². the spring have for its deflection to be 6 mm. (16)
14. (a) Using Moment area method, derive an expression for deflection of a simply supported beam subjected to uniformly distributed load for entire span. (16)

Or

- (b) A beam AB of length 8 m is simply supported at its ends and carries two point loads of 50 kN and 40 kN at a distance of 2 m and 5 m respectively from left support A. Determine, deflection under each load, maximum deflection and the position at which maximum deflection occurs. Take $E = 2 \times 10^5$ N/mm² and $I = 8.5 \times 10^6$ mm⁴. (16)

15. (a) A point in a strained material the horizontal tensile stress is 80 N/mm^2 and the vertical compressive stress is 140 N/mm^2 . The shear stress is 40 N/mm^2 . Find the principal stresses and the principal planes. Find also the maximum shear stress and its planes. (16)

Or

- (b) At a point within a body subjected to two mutually perpendicular directions, the stresses are 180 N/mm^2 (tensile) and 100 N/mm^2 (compressive). Each of the above stresses is accompanied by a shear stress of 50 N/mm^2 . Determine
- (i) major and minor principal stresses and its direction
 - (ii) maximum shear stress
- (16)
-

