

C

Reg. No. :

--	--	--	--	--	--	--	--	--	--	--

**Question Paper Code: 99121**

B.E./B.Tech. DEGREE EXAMINATION, MAY 2024

Elective

Civil Engineering

19UCE921- Structural Design And Drawing

(Regulations 2019)

Duration: Three hours

Maximum: 100 Marks

PART A - (5x 20 = 100 Marks)

1. (a) Design a stem of a Cantilever retaining wall to retain 6m of horizontal backfill. The Density of the soil is  $18\text{kN/m}^3$   
Safe Bearing Capacity of the Soil= $200\text{kN/m}^2$   
Angle of internal Friction of Soil= $30^\circ$   
The Coefficient of friction between base slab and concrete= $0.55$   
Use M20 concrete and Fe415 Steel.  
Draw cross sectional view of stem. And also check the stability. CO1-App (16)
- Or
- (b) Design stem of a Cantilever retaining wall to retain 4m of horizontal backfill CO1-App (16)  
The Density of the soil is  $18\text{kN/m}^3$   
Safe Bearing Capacity of the Soil= $200\text{kN/m}^2$   
Angle of internal Friction of Soil= $30^\circ$   
The Coefficient of friction between base slab and concrete= $0.55$   
Use M20 concrete and Fe415 Steel.  
Draw cross sectional view of stem. And also check the stability.
2. (a) Design an underground tank of internal dimensions 8 m x 2 m x 2m. the soil surrounding the tank is likely to get wet. Angle of repose of soil in dry state is  $30^\circ$  and in wet state is  $60^\circ$  soil weighs  $20\text{ KN/m}^3$  CO2- App (16)

Or

- (b) Design a circular water tank with fixed base for capacity of 400000 liters. The depth of water is to be 4m. free board = 200 mm. Use M-20 grade of concrete and Grade I mild steel.  
Permissible direct tensile stress in concrete = 1.2 N/mm<sup>2</sup>  
Permissible stress in steel in direct tension = 100 N/mm<sup>2</sup>  
Sketch the details of reinforcements in tank walls.  
Adopt IS code Tables for coefficients. CO2-App (16)
3. (a) Design A Rectangular R.C water tank with an open top is required to store 80000 litres of water. The inside dimensions of tank may be taken as 6mX4m. The tank rests on all four sides. Design the side walls of the tank using M-20 concrete and grade I steel. CO2-App (16)  
Permissible stresses  
 $\sigma_{cb} = 7 \text{ N/mm}^2$   
 $\sigma_{st} = 100 \text{ N/mm}^2$  (on faces near water face)  
 $\sigma_{st} = 125 \text{ N/mm}^2$  (on faces away from water face)  
 $m = 13 \quad Q = 1.41 \quad J = 0.84$   
Or
- (b) Design a circular water tank with fixed base for capacity of 400000 liters. The depth of water is to be 4m. free board = 200 mm. Use M-20 grade of concrete and Grade I mild steel.  
Permissible direct tensile stress in concrete = 1.2 N/mm<sup>2</sup>  
Permissible stress in steel in direct tension = 100 N/mm<sup>2</sup>  
Sketch the details of reinforcements in tank walls.  
Adopt IS code Tables for coefficients. CO2-App (16)
4. (a) Design an underground tank of internal dimensions 8 m x 2 m x 2m. the soil surrounding the tank is likely to get wet. Angle of repose of soil in dry state is 30° and in wet state is 60° soil weighs 20 KN/m<sup>3</sup> CO2-App (16)  
Or
- (b) Write down the design procedure of a circular water tank is resting on the ground. CO2-App (16)

5. (a) A beam-column of effective length of 6 m carries an axial load of 450 KN and equal end moments of 50 KN-m each about the major axis. Design the H-Section of the Column. Assume that members in the frame where side sway is prevented and not subjected to transverse loading between their supports and column bends either in single or in double curvature. CO3-App (16)

Or

- (b) Design an I-section purlin, for an industrial building situated in the outskirts of Kolkata, to support a galvanized iron sheet roof for the following data: CO3-App (16)

Slope of truss =  $30^\circ$ , Spacing of truss c/c = 5.0 m

Span of truss = 12.0 m , spacing of purlins c/c = 2 m

wind speed = 50 m/s ,Weight of galvanized sheets = 120 N/m<sup>2</sup>

Grade of steel = Fe 410

