	Ttog. 1 to 1						
	Question Pap	per Code: U3'	704				
	B.E./B.Tech. DEGREE EX	AMINATION, A	PRIL 20)24			
	Third S	Semester					
	Mechanical	Engineering					
	21UME304 – FLUID MECH	ANICS AND MA	CHINE	RY			
	(Regulat	ions 2021)					
Dur	ration: Three hours	Maximum: 100 Marks					
	Answer AL	L Questions					
	PART A - (10	x 1 = 10 Marks)					
1.	In one dimensional flow, the flow					CC	01 - U
	(a) Is steady and uniform	(b) takes place	e in strai	ight line			
	(c) takes place in curve	(d) takes place	e in one	direction			
2.	Which of the following is an example of lan	ninar flow?				CO	01 - U
	(a) Underground flow	(b) Flow past	tiny bod	lies			
	(c) Flow of oil in measuring instruments	(d) All of the	above.				
3.	The coefficient of viscosity may be determin	ed by				CC	01 - U
	(a) Capillary tube method	(b) Orifice tube	viscom	eter			
	(c) Rotating cylinder method	(d) All of the ab	oove				
4.	Which property of the fluid accounts for the	major losses in p	ipes?			CC	01 - U
	(a) Density (b) Specific gravity	(c) Viscosity		(d) Co	mpres	sibil	ity
5.	Dynamic viscosity (μ) has the dimensions a	S				CC	01 - U
	(a) MLT^{-2} (b) $ML^{-1}T^{-1}$	$(c)ML^{-1}T^{-2}$		$(d) M^{-1}$	$L^{-1}T^{-1}$		
6.	Surface tension has the units of					CC	01 - U
	(a) force per unit area	(b) force per un	it length	1			
	(c) force per unit volume	(d) none of the	above				
7.	is the electric power obta	ined from the ener	rgy of th	ne water.		CO	01 - U
	(a) Roto dynamic power	(b) Thermal pow	/er				
	(c) Nuclear power	(d) Hydro electri	ic power	ſ			

8.	In a Kaplan turbine runner the number of blades are generally between					CO1- U		
	(a) 2	2 to 4	(b) 4 to 8	(c) 8 to 16	(d) 16 to 24			
9.	The specific speed of a centrifugal pump, delivering 750 litres of water per second against a head of 15 metres at 725 r.p.m is					CO1- U		
	(a) 2	24.8 r.p.m	(b) 24.8 r.p.m	(c) 82.4 r.p.m	(d) 248 r.p.m			
10.	Which of the following is NOT a type of positive displacement pumps?					CO1- U		
	(a) Reciprocating pump (b) dummy pump							
	(c) (Centrifugal pump		(d) None of these				
			PART – B (5 x 2= 10Marks)				
11.	Desc	escribe capillarity with its units.				1- U		
12.	Explain the difference between laminar and turbulent flow.					CO1- U		
13.	Mention Buckingham's π – Theorem.					CO1- U		
14.						CO1- U		
15.	Explain the Slip of reciprocating pump.					CO1- U		
			PART – C	(5 x 16= 80 Marks)				
16.	(a)	(3/2)y - y3/2, w meter above the	here u is the point	a flat plate is given by u velocity in m/s at a distance the shear stress at $y = 9cr$	у	(16)		
	(b)	between a squar with angle of in 300N and it slide	namic viscosity of oie plate of size 0.8m nclination 30°. The	l, which is used for lubrication X 0.8m and an inclined plan weight of the square plate plane with a uniform velocity m is 1.5mm	ne is	(16)		
17.	(a)	15cm at section pipe is 40 liters section-2 is 3m	s 1 and 2 respectives/sec. The section-1	e having diameters 20cm arely. The rate of flow through is 6m above the datum arely the pressure at section-1 essure at section-2.	gh id	(16)		
	(b)	Derive Bernoulli		ler's Equation with a neat ske	etcl CO6-App	(16)		

- 18. (a) The efficiency (η) of a fan depend on density (ρ) , dynamic CO4- App viscosity (μ) of the fluid, angular velocity (ω) , diameter (D) of the rotor and discharge (Q). Express η in terms of dimensionless parameters. Using Buckingham's π theorem.
 - (b) The resisting force (R) of a supersonic plane during flight can be CO4- App considered as dependent upon the length of aircraft (l), velocity (V), dynamic viscosity of air (μ), air density (ρ) and bulk modulus of air (K). Express the functional relationship between these variables and the resisting force using Buckingham's π Theorem.
- 19. (a) A Pelton Wheel is having a mean bucket diameter of 1m and is CO7- App running at 1000rpm. The net head on the Pelton Wheel is 700m. If the side clearance angle is 15° and discharge through nozzle is 0.1m³/s. Find (i) Power available at the nozzle (ii) Hydraulic efficiency of the turbine.

Or

- (b) A Kaplan Turbine working under a head of 20m develops CO7-App (16) 11772KW shaft power. The outer diameter of the runner is 3.5m and hub diameter 1.75m. The guide blade angle at the extreme edge of the runner is 35°. The hydraulic and overall efficiencies of the turbines are 88% and 84% respectively. If the velocity of whirl is zero at outlet, determine (i) Runner vane angles at inlet and outlet at the extreme edge of the runner (ii) Speed of the turbine.
- 20. (a) Explain the working principle of Single acting & Double acting CO1- U (16) Reciprocating pump with a neat sketch.

O₁

(b) Explain the working principle of Gear Pump and Vane Pump with CO1- U the neat sketch. (16)