A
\mathbf{A}
_

Reg. No.:					

Question Paper Code: 55303

B.E./B.Tech. DEGREE EXAMINATION, MAY 2022

Fifth Semester

Electrical and Electronics Engineering

Electrical and Electronics Engineering							
15UEE503- Microprocessors and Microcontroller Programming							
	(Regulation 2015)						
Dura	Duration: Three hours Maximum: 100 Marks						
		Answer Al	LL Questions				
		PART A - (10	x 1 = 10 Marks)				
1.	When an 8085 micro	oprocessor is reset, the	e address bus contains		CO1- R		
	(a) 0000H	(b) 0002H	(c) 0043H	(d) 003C H			
2.	A microprocessor is functions of a CPU o		chip integrating all the		CO1- R		
	(a) Multiple	(b) Single	(c) Double	(d) Triple			
3.	In 8085 microprocessor, the RST6 instruction transfer programme execution to following location						
	(a) 0030H	(b) 0024H	(c) 0048H	(d) 0060H			
4.	Why do the micropro	ocessors possess very	few bit manipulating instru	ections?	CO2- R		
	(a) Because they mostly operate on bits/ word data						
	(b) Because they mostly operate on byte/word data						
	(c) Both a & b						
(d) None of the above							
5.	5. The registers that contain the status information is C O3-						
	(a) Control registers (b) Control registers						
	(c) Program status word (d) All of the mentioned						

6.	The	internal RAM m	nemory of the 8051 is			CO3- F	
	(a) 3	32 bytes	(b) 64 bytes	(c) 128 bytes	(d) 256 byte	S	
7.			reset and the \overline{EA} line first program instruct	e is HIGH, the program ion in the		CO4- F	
	(a) I	internal code men	mory	(b) External code memor	y		
	(c) I	nternal data men	nory	(d) External data memory	1		
8.		Which components are not found on chip in a microprocessor but may be found on chip in a microcontroller					
	(a) E	EPROM,USART	&PORTS	(b) EPROM & PORTS			
	(c) S	SRAM &USART		(d) SRAM,EPROM &PORTS			
9.			roups of 8051 regist ecessed at a time is	er banks, the number of		CO5- F	
	(a) 1	1	(b) 2	(c) 3	(d) All of the	e above	
10.	The	operations perfo	rmed by data transfer	instructions are on		CO5- F	
	(a) b	oit data	(b) byte data	(c) 16 bit data	(d) All of the	e above	
			PART – B (5	x 2= 10 Marks)			
11.		e any four pins us signals.	of 8085 processor w	rhich are used to generate	control and	CO1- F	
12.	Exp	lain the function	ing of CMP instructio	n.		CO2- F	
13.	How multiplication is performed in 8085 and 8051?						
14.	Write down the control word of 8255 if port A is configured as input and port B is configured as output in mode 0.						
15.	Spec	cify the difference	e between MOV and	MOVX instructions.		CO5- F	
			PART – C	(5 x 16= 80 Marks)			
16.	(a)	With the neat blocks of 8085		various functional buildin	g CO1-U	(16)	
			Or				
	(b)			various interrupts of 808 errupt service routine.	5 CO1-U	(16)	

17.	(a)	Define addressing mode. Identify the addressing mode and number of bytes of the following instructions and Discuss them	CO2- C	(16)
		(i) LDA 8300H (ii) MOV A,B (iii) MVI B,FFH (iv) MOV B,M (v) IN 80H (vi) CMA		
		Or		
	(b)	Draw the flowchart and write an assembly language program to sort 100 bytes of data using 8085 processor.	CO2- C	(16)
18.	(a)	Draw and explain the pin out configuration of 8051 microcontroller.	CO3- U	(16)
		Or		
	(b)	Explain the interrupt structure of 8051 microcontroller and also explain how interrupts are prioritized.	CO3- U	(16)
19.	(a)	Draw the functional diagram of 8255 and explain its control word and various modes of operation.	CO4- U	(16)
		Or		
	(b)	Explain the interfacing of DAC with 8085 processor with neat diagram and write an assembly programme to generate a typical waveform.	CO4- U	(16)
20.	(a)	Draw the schematic for interfacing a stepper motor with 8051 microcontroller and write an ALP for changing speed and direction of motor.	CO5- U	(16)
		Or		
	(b)	With a neat circuit diagram explain how a 4 x 4 keypad and seven segment display is interfaced with 8051 microcontroller.	CO5- U	(16)