

A

Reg. No. :

--	--	--	--	--	--	--	--	--	--

Question Paper Code: 94704

B.E. / B.Tech. DEGREE EXAMINATION, MAY 2022

Fourth Semester

Mechanical Engineering

19UME404 - Mechanics of Materials

(Regulations 2019)

Duration: Three hours

Maximum: 100 Marks

Answer ALL Questions

PART A - (10 x 1 = 10 Marks)

1. The ratio of tensile stress to the tensile Strain is known as ____ CO1- U
(a) Young's Modulus (b) Poisson's ratio (c) Stress (d) Strain
2. A material which recovers fully after unloading is known as CO1- U
(a) Plastic (b) Elastic (c) In Elastic (d) partially elastic
3. In a cantilever, carrying a load whose intensity varies uniformly from zero at the free end to weight per unit run at the fixed end, the BM changes following a CO1- U
(a) linear law (b) Parabolic law (c) cubic law (d) none of the above
4. BM at supports in case of simply supported beams is always CO1- U
(a) Less than unity (b) More than unity (c) Zero (d) none of the above
5. In the torsion equation $T/J = \tau/R = C\theta/L$, the term J/R is called _ CO1- U
(a) Shear Modulus (b) Section modulus (c) Polar modulus (d) None of these
6. The polar moment of inertia of a hollow shaft of outer diameter (D) and inner diameter (d) is CO1- U
(a) $\pi/16(D^3-d^3)$ (b) $\pi/16(D^4-d^4)$ (c) $\pi/32(D^4-d^4)$ (d) $\pi/64(D^4-d^4)$
7. The column which has highest equivalent length has ____ CO1- U
(a) one end fixed other pin joined (b) both ends fixed
(c) both ends hinged (d) one end fixed other end free

8. All short columns fails by ----- CO1- U
 (a) Crushing (b) Elongation (c) Bending (d) twisting
9. A thin cylindrical shell of diameter (d), length (l) is subjected to an internal pressure (p). The circumferential stress of the shell is ____ CO1- U
 (a) bulk removal (b) minimum removal
 (c) surface finishing (d) none of the above
10. Which of the following are usually considered as thin cylinders? CO1- U
 (a) Boilers (b) Tanks (c) Steam pipes (d) Water pipes

PART – B (5 x 2= 10 Marks)

11. Explain what is stress? CO1- U
12. Explain what is cantilever beam? CO1- U
13. Define polar modulus. CO1- U
14. State the limitation of Euler's formula. CO1- U
15. Define Hoop stress and longitudinal stress. CO1- U

PART – C (5 x 16= 80 Marks)

16. (a) A mild steel rod of 20 mm diameter and 300 mm long is enclosed centrally inside a hollow upper tube of external diameter 30 mm and internal diameter of 25 mm. The ends of the tube and rods are brazed together and the composite bar is subjected to an axial pull of 40 kN. If E for steel and copper is 200 GN/m^2 and 100 GN/m^2 respectively, find the stresses developed in the rod and tube. Also, find the extension of the rod. CO2- App (16)
- Or
- (b) A reinforced concrete column 500mm X 500mm in section is reinforced with 4 steel bars of 20mm diameter, one in each corner. The column is carrying a load of 750kN. Determine the stress in concrete and steel bars. Take E for steel as 210 GPa and for concrete as 14 GPa. Also calculate load carried by steel and concrete. CO1- U (16)

17. (a) A Cantilever 3.6 m long carries load of 30 KN, 70 KN, 40 KN and 60 KN at distance of 0, 0.6, 1.5 and 2.4 m respectively from the free end. Draw the SF and BM diagrams for the cantilever CO2- App (16)
- Or
- (b) Draw the SF and BM diagram for a simply supported beam of span 9 m. The beam carries a UDL of 10 KN/m for a distance of 6 m from the left support. Find the maximum value and their position. Give the values at important points in the diagram CO2- App (16)
18. (a) Find the diameter of a solid circular shaft to transmit 150 KW of power at 300 rpm. If the allowable shear stress is 90 MPa and twist is 1° over 2 m length of the shaft. Take rigidity modulus as 90 GPa. CO2- App (16)
- Or
- (b) A solid shaft is to transmit 300 KW at 100rpm if the shear stress is not to exceed 80N/mm². Find the diameter of the shaft. If this shaft is to be replaced by hollow shaft of same material and length with an internal diameter of 0.6 times the external diameter, what percentage saving in weight is possible? CO2- App (16)
19. (a) A steel 8 m long and 80mm in diameter is used a column determine the crippling load by using Euler's formula when the column is used in any three end conditions. $E = 2.1 \times 10^5 \text{ N/mm}^2$. CO2- App (16)
- Or
- (b) A hollow cast iron column whose outside diameter is 200 mm has a thickness of 20 mm. The length of the column is 4.5 m with both of its fixed. Calculate the safe load for the column using Rankine's formula. Also calculate the ratio of Euler's crippling load to that of Rankine's critical load. Take factor of safety as 4. $f_c = 550 \text{ N/mm}^2$, $\alpha = 1/1600$ and $E = 94 \text{ kN/mm}^2$. CO2- App (16)

20. (a) A cylinder has internal diameter of 230 mm, wall thickness 5 mm and is 1 m long. It is found to change in internal volume by $12 \times 10^{-6} \text{ m}^3$ when filled with a liquid at a pressure 'p'. Taking $E = 200 \text{ GPa}$ and Poisson's ratio = 0.25, determine the stresses in the cylinder, the changes in its length and internal diameter. CO2- App (16)

Or

- (b) A cylindrical shell 1 m internal diameter and 15 mm wall thickness is 3 m long. Calculate the maximum intensity of shear stress induced and also the changes in the dimensions of the shell if it is subjected to an internal pressure of 1.5 N/mm^2 . Take $E = 2.04 \times 10^5 \text{ N/mm}^2$ and $\nu = 0.3$. CO2- App (16)