C

Reg. No. :

Question Paper Code: 95403

B.E. / B.Tech. DEGREE EXAMINATION, NOV 2022

Fifth Semester

Electronics and Communication Engineering

	19	UEC503 - Data Commu	inication and Networ	ks		
		(Regulation	ns 2019)			
Duration: Three hours Maximum: 100						
		Answer ALL	Questions			
		PART A - (5 x 1	1 = 5 Marks)			
1.	1. Which address identifies a process on a host?					
	(a) Physical address	(b) Logical address	(c) Port address	(d) Specif	fic address	
2.		adding a special byte to character with the same			CO1- U	
3.	(a) Header How many bytes are	(b) Trailer. empty in a RIP message	(c) Flag that advertises N ne	(d) None of the tworks?	ne above CO1- U	
	(a) $2 + (10 \times N)$	(b) 2×N	(c) $2 \times (10 + N)$	(d) 2^N		
4. If the receiver window size is 12 MSS, then the SS_{thresh} will be						
	(a) 5 MSS	(b) 8 MSS	(c) 6 MSS	(d) 12 MSS	S	
5.	In the DNS, the name	es are defined in	structure.		CO1- U	
	(a) A linear list.	(b) An inverted-tree.	(c) A graph.	(d) A List		
$PART - B (5 \times 3 = 15 \text{ Marks})$						
6.	What is multipoint connection? How it is related to Bus topology? CO1-					
7.	A CSMA/CD bus spans a distance of 1.5 km. If the data rate is 5 Mbps what is the minimum frame size?					
8.	If a router has 20 entries in its group table, should it send 20 different queries periodically or just one? Explain your answer.					
9.	Discuss about Deadlo	ock situation in congesti	on.		CO1-U	

CO1 U

10. Explain how HTTP is related to WWW and FTP.

$PART - C (5 \times 16 = 80 \text{ Marks})$

11. (a) Discuss the different network topologies in detail, with their CO1-U (16)Performance indicators. Or(b) Discuss in detail about OSI model with neat sketch. CO1-U (16)12. (a) Draw and explain the frame structure of IEEE 802.3. Also find the CO2- App (16)minimum frame length for a network of 5 nodes connected using 10 Base T cable. Assume the total propagation delay the network is 50microsec. Or (b) In a CDMA/CD network with a data rate of 10 Mbps, the CO2-App (16)minimum frame size is found to be 512 bits for the correct operation of the collision detection process. What should be the minimum frame size if we increase the data rate to (a) 100 Mbps? (B) 1 Gbps? (C) 10 Gbps? 13. (a) A router with IPv4 address 125.45.23.12 and Ethernet physical CO2-App (16)address 23:45:AB:4F:67:CD has received a packet for a host destination with IP address 125.11.78.10. Show the entries in the ARP request packet sent by the router and also ARP Packet sent in response. Assume no sub netting. Or (b) Show the autonomous system with the following specifications: CO2-App (16)There are eight networks (NI to N8), eight routers (RI to R8), NI, N2, N3, N4, NS, and N6 are Ethernet LANs, N7 and N8 are pointto-point WANs, RI connects NI and N2, R2 connects NI and N7, R3 connects N2 and N8, R4 connects N7 and N6, RS connects N6 and N3,R6 connects N6 and N4,R7 connects N6 and NS,R8 connects N8 and N5. Draw the graphical representation of the autonomous system as seen by OSPF 14. (a) CO1-U (8)(i) Explain leaky bucket and token bucket algorithms in detail.

Or

connection termination with neat diagrams.

(b) Discuss the various timers used by TCP to perform its various CO1-U (16) operations

(ii) Explain in detail about TCP connection establishment and CO1-U

(8)

15. (a) Explain in detail about Electronic mail. CO1- U (16)
Or
(b) Briefly Explain the steps involved in RSA algorithm. CO1- U (16)