

Reg. No. :

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Question Paper Code: R3D01

B.E./B.Tech. DEGREE EXAMINATION, NOV 2025

Third Semester

Computer Science and Business Systems

R21UCB301–FORMAL LANGUAGE AND AUTOMATA THEORY

(Regulations R2021)


Duration: Three hours

Maximum: 100 Marks

Answer ALL Questions

PART A - (10 x 2 = 20 Marks)

1. Construct NFA to accept all strings contains $\{a,b\}$ which starting with “abb”. CO1- U
2. Construct a DFA that recognize the strings of $\{0,1\}$ that do not contain the substring 101. CO6- App
3. Convert the following Finite Automata to Regular Grammar CO2- App



4. List out the closure properties of Regular Language. CO2- Ana
5. List out the applications of Context Free Grammar. CO6- Ana
6. Remove ϵ production from the given context free grammar CO6- U
 $S \rightarrow XYX, X \rightarrow 0X | \epsilon, y \rightarrow 1Y | \epsilon$
7. Define the formal definition of Linear Bounded automata. CO6- U
8. Construct a PDA equivalent to CFG CO6- U
 $S \rightarrow 0BB, B \rightarrow 0S | 1S | 0$
9. What do you mean by Universal Turing Machine? CO2- U
10. Define Diagonalization language (L_d). CO2- U


PART – B (5 x 16= 80 Marks)

11. (a) Construction of NFA to DFA using Subset construction methods. CO1-App (16)


	a	b
P	{p,q}	{p}
Q	{r}	{r}
R	{s}	-
*s	{s}	{s}

Or

- (b) Construction of NFA to DFA using subset Construction methods CO1-App (16)




12. (a) Find regular expression for the following DFA using State Elimination method. CO2- App (16)



Or

- (b) Find regular expression for the following DFA using Arden's Theorem CO2- App (16)



13. (a) (i) Simplify the following grammar and find its equivalent in CNF. CO2-App (16)
 $S \rightarrow bA \mid aB$,
 $A \rightarrow bAA \mid aS \mid a$,
 $B \rightarrow aBB \mid bS \mid b$ (12)
(ii) Show that the grammar $S \rightarrow SbS \mid a$ is ambiguous or not for the string $W = ababa(4)$

Or

- (b) (i) Convert the following CFG to GNF CO2-App (16)
 $S \rightarrow a \mid aA \mid B$
 $A \rightarrow aBB \mid \epsilon$
 $B \rightarrow Aa \mid b$

14. (a) Convert the PDA $M = (\{q_0, q_1\}, \{0, 1\}, \{X, Z_0\}, \delta, q_0, Z_0, \Phi)$ into CO1-App (16)
Grammar. Where δ is defined as
a. $\delta(q_0, 0, Z_0) = (q_1, XZ_0)$
b. $\delta(q_0, 0, X) = (q_1, XX)$
c. $\delta(q_0, 1, X) = (q_1, \epsilon)$
d. $\delta(q_1, 1, X) = (q_1, \epsilon)$
e. $\delta(q_1, \epsilon, X) = (q_1, \epsilon)$
f. $\delta(q_1, \epsilon, Z_0) = (q_1, \epsilon)$

Or

- (b) (i) Construct PDA for the Language $L = \{0^m 1^m \mid m \geq 1\}$ (8) CO1-App (16)
(ii) Convert the following CFG to Push Down Automata. (8)
 $S \rightarrow aDB$
 $A \rightarrow aD$
 $B \rightarrow b$
 $D \rightarrow a$
 $C \rightarrow a$

15. (a) Construct Turing Machine for the Language $L = \{a^n b^n\}$ where $n \geq 1$. CO2-App (16)

Or

- (b) Construct the TM to validate $L = \{a^m b^m c^m \mid m \geq 1\}$ CO2-App (16)

